


- High Density Resistor Simulation
- Fitted With Pickering Reed Relays, Providing Superior Speed of Operation & Card Life
- Up to 18 Channels on a Single Card
- Resistance Resolution to 0.125Ω
- Values From 2Ω to 22MΩ
- Accuracy of ±0.2% ± Resolution
- Short and Open Simulation
- Simple Software Control Through Resistance Calls
- VISA & Kernel Drivers Supplied for Windows
- 3 Year Warranty




The 50-298 provides a simple solution for applications requiring accurate simulation of resistive sensors. It is available in a variety of resistance ranges and resolutions to meet the needs of functional test systems. It is suitable for engine controller testing where resistive sensors provide information such as temperature.

The 50-298's channels are able to be set as short or open circuit to simulate a wiring or sensor fault.

Software control is simplified by the use of resistor value calls. The card works out the channel setting closest to the requested value and sets that value. The user can interrogate the card to find the actual resistance setting used.

A calibration cable can be attached to the card allowing a DMM to be used to verify each channel. This considerably simplifies the checking of the card's calibration.


Verification is performed with the UUT disconnected from the card.



Pickering's Range of PCI Resistor Cards					
Model	Description	Chan.	Range	Resolution	Accuracy
50-262	RTD Simulator	6	350Ω, 1kΩ, 1.5kΩ, 2kΩ or 3kΩ	<8mΩ or <90mΩ	0.1%
50-265	Strain Gauge Simulator	6	350Ω, 1kΩ, 1.5kΩ, 2kΩ or 3kΩ	<2mΩ, <10mΩ, <12.5mΩ, <20mΩ or <25mΩ	0.03% or 0.06%
50-293	Programmable Resistor + SPDT	2 or 4	Up to 131kΩ	0.25Ω, 0.5Ω, 1Ω or 2Ω	1% ±Resolution
50-294	Programmable Resistor + SPST	2 or 4			
50-295	Programmable Resistor	3, 6, 5, 10 or 18	Up to 16MΩ	8, 12, 16 or 24-Bit	±0.5% (1% >1MΩ)
50-296	Programmable Potentiometer	1, 2, 3, 4, 5 or 9			
50-297	High Density Precision Resistor	3, 4, 6, 9 or 18	Up to 22.3MΩ	0.125Ω, 0.25Ω, 0.5Ω, 1Ω or 2Ω	0.2%
50-298	High Density Precision Resistor	3, 4, 6, 9 or 18	Up to 22.3MΩ	0.125Ω, 0.25Ω, 0.5Ω, 1Ω or 2Ω	0.2%
Custom Resistor Cards					
If our range of Resistor Cards does not meet your specific requirements, please contact your local sales office to discuss your application. Customizations include: different start and stop values, current, power, voltage, precision, accuracy, number of channels, connector etc.					

The 50-298 is available in 50 standard builds that suit the most common configurations required:

- A narrow resistance range version with 9 or 18 channels.
- A medium resistance range version with 4 or 9 channels.
- A wide resistance range version with 3 or 6 channels.



PXI Part Number (Number of Channels)	Resistance Range									Resolution
	1Ω	10Ω	100Ω	1kΩ	10kΩ	100kΩ	1MΩ	10MΩ	100MΩ	
50-298-010 (18) 50-298-110 (9)	[Red bar from 10Ω to 100Ω]									0.125Ω
50-298-011 (18) 50-298-111 (9)	[Red bar from 10Ω to 1kΩ]									0.25Ω
50-298-012 (18) 50-298-112 (9)	[Red bar from 10Ω to 10kΩ]									0.5Ω
50-298-013 (18) 50-298-113 (9)	[Red bar from 10Ω to 100kΩ]									1Ω
50-298-014 (18) 50-298-114 (9)	[Red bar from 10Ω to 1MΩ]									2Ω
50-298-020 (9) 50-298-120 (4)	[Red bar from 10Ω to 10kΩ]									0.125Ω
50-298-021 (9) 50-298-121 (4)	[Red bar from 10Ω to 100kΩ]									0.25Ω
50-298-022 (9) 50-298-122 (4)	[Red bar from 10Ω to 1MΩ]									0.5Ω
50-298-023 (9) 50-298-123 (4)	[Red bar from 10Ω to 10MΩ]									1Ω
50-298-024 (9) 50-298-124 (4)	[Red bar from 10Ω to 100MΩ]									2Ω
50-298-030 (9) 50-298-130 (4)	[Red bar from 10Ω to 10kΩ]									0.125Ω
50-298-031 (9) 50-298-131 (4)	[Red bar from 10Ω to 100kΩ]									0.25Ω
50-298-032 (9) 50-298-132 (4)	[Red bar from 10Ω to 1MΩ]									0.5Ω
50-298-033 (9) 50-298-133 (4)	[Red bar from 10Ω to 10MΩ]									1Ω
50-298-034 (9) 50-298-134 (4)	[Red bar from 10Ω to 100MΩ]									2Ω
50-298-040 (6) 50-298-140 (3)	[Red bar from 10Ω to 10kΩ]									0.125Ω
50-298-041 (6) 50-298-141 (3)	[Red bar from 10Ω to 100kΩ]									0.25Ω
50-298-042 (6) 50-298-142 (3)	[Red bar from 10Ω to 1MΩ]									0.5Ω
50-298-043 (6) 50-298-143 (3)	[Red bar from 10Ω to 10MΩ]									1Ω
50-298-044 (6) 50-298-144 (3)	[Red bar from 10Ω to 100MΩ]									2Ω
50-298-050 (6) 50-298-150 (3)	[Red bar from 10Ω to 10kΩ]									0.125Ω
50-298-051 (6) 50-298-151 (3)	[Red bar from 10Ω to 100kΩ]									0.25Ω
50-298-052 (6) 50-298-152 (3)	[Red bar from 10Ω to 1MΩ]									0.5Ω
50-298-053 (6) 50-298-153 (3)	[Red bar from 10Ω to 10MΩ]									1Ω
50-298-054 (6) 50-298-154 (3)	[Red bar from 10Ω to 100MΩ]									2Ω

Graphical Representation of the 50-298 Precision Resistor Card Range

Relay Type

The 50-298 is fitted with Pickering reed relays with sputtered ruthenium contacts. A spare relay is built onto the circuit board to allow easy maintenance with minimum downtime.

Specification

Accuracy:	0.2% ±Resolution @ ±10°C from calibration temperature (factory calibration @ 21°C)
Fault Simulation:	Open and short circuit (typically <0.5Ω)
Max Power:	0.5W
Max Voltage:	100V* or as limited by power
Thermal Offset:	<100µV
Settling Time:	0.5ms †
Software Control:	By resistance calls to card for selected channel.
Calibration:	4-wire resistance measurement of selected channel for verification purposes with UUT removed and a special cable assembly attached. Factory calibration data is stored in the card.
Expected Life (operations):	1000 million (10mA)

* For full voltage rating, signal sources must be fully isolated from mains supply and safety earth.

† The total operate time when setting a resistance may be longer depending upon the change requested due to relay sequencing.

Power Requirements

+3.3V	+5V	+12V	-12V
0.2A	0.9A max	0	0

Mechanical Characteristics

Single slot short PCI format.

3D models for all versions in a variety of popular file formats are available on request.

Connectors

Resistor connections via a 37-pin male D-Type connector. For pin outs please refer to the operating manual.

PCI Compliance

The 50-298 complies with the PCI Specification 2.0 (issued Feb 2004).

Signalling Environment: 33MHz, 32-bit Universal (+3.3V & +5V).

For advance information about a PCI Express version of this card please contact your local Pickering sales office

Supplied soft front panels and driver software are fully compatible with Windows operating systems.

Safety & CE Compliance

All cards are fully CE compliant and meet applicable EU directives: Low-voltage safety EN61010-1:2010, EMC Immunity EN61326-1:2013, Emissions EN55011:2009+A1:2010.

Operating/Storage Conditions

Operating Conditions

Operating Temperature:	0°C to +55°C
Humidity:	Up to 90% non-condensing
Altitude:	5000m

Storage and Transport Conditions

Storage Temperature:	-20°C to +75°C
Humidity:	Up to 90% non-condensing
Altitude:	15000m

Product Order Codes

0.125Ω Resolution

Range	No. of Channels	Order Code	No. of Channels	Order Code
2Ω to 31.5Ω	9	50-298-110	18	50-298-010
2.5Ω to 472Ω	4	50-298-120	9	50-298-020
3Ω to 6.97kΩ	4	50-298-130	9	50-298-030
3.5Ω to 102kΩ	3	50-298-140	6	50-298-040
4Ω to 1.51MΩ	3	50-298-150	6	50-298-050

0.25Ω Resolution

Range	No. of Channels	Order Code	No. of Channels	Order Code
2Ω to 62.1Ω	9	50-298-111	18	50-298-011
2.5Ω to 925Ω	4	50-298-121	9	50-298-021
3Ω to 13.6kΩ	4	50-298-131	9	50-298-031
3.5Ω to 201kΩ	3	50-298-141	6	50-298-041
4Ω to 2.97MΩ	3	50-298-151	6	50-298-051

0.5Ω Resolution

Range	No. of Channels	Order Code	No. of Channels	Order Code
2Ω to 122Ω	9	50-298-112	18	50-298-012
2.5Ω to 1.81kΩ	4	50-298-122	9	50-298-022
3Ω to 26.7kΩ	4	50-298-132	9	50-298-032
3.5Ω to 395kΩ	3	50-298-142	6	50-298-042
4Ω to 5.82MΩ	3	50-298-152	6	50-298-052

1Ω Resolution

Range	No. of Channels	Order Code	No. of Channels	Order Code
2Ω to 239Ω	9	50-298-113	18	50-298-013
2.5Ω to 3.55kΩ	4	50-298-123	9	50-298-023
3Ω to 52.4kΩ	4	50-298-133	9	50-298-033
3.5Ω to 773kΩ	3	50-298-143	6	50-298-043
4Ω to 11.4MΩ	3	50-298-153	6	50-298-053

2Ω Resolution

Range	No. of Channels	Order Code	No. of Channels	Order Code
2Ω to 470Ω	9	50-298-114	18	50-298-014
2.5Ω to 6.97kΩ	4	50-298-124	9	50-298-024
3Ω to 102kΩ	4	50-298-134	9	50-298-034
3.5Ω to 1.51MΩ	3	50-298-144	6	50-298-044
4Ω to 22.3MΩ	3	50-298-154	6	50-298-054

Accessories:

Calibration lead for 4-wire resistance measurement using DMM - 37-pin D-type socket to shrouded 4mm bayonet plugs.

1 meter length: 40-975-037-1m

Adapter to convert from male 37-pin D-type to male 78-pin D-type, converting from 2-wire to 4-wire channel connections.

Please contact your local sales office for details.

Mating Connectors & Cabling

For connection accessories for the 50-298 series please refer to the [90-007D](#) 37-pin D-Type Connector Accessories data sheet where a complete list and documentation can be found for accessories, or refer to the Connection Solutions catalog.

Other Resistor Cards

Pickering Interfaces manufacture a range of variable resistor cards in the PCI format. If you have a requirement for a variable resistor card please contact your local sales office with the information below and we will advise you on the best solution for your application.

Lowest Resistance †	<input type="text"/>
Highest Resistance	<input type="text"/>
Resistance Resolution	<input type="text"/>
Overall Accuracy	<input type="text"/>
Maximum Power/Current	<input type="text"/>
Number of Channels (variable resistors)	<input type="text"/>

† Resistance is as measured across the user connector terminals, minimum resistance must have a non-zero value.

Product Customization

Pickering PCI cards are designed and manufactured on our own flexible manufacturing lines, giving complete product control and enabling simple customization to meet very specific requirements.

Customization can include:

- Alternative resistance range
- Alternative resolution
- Different number of channels
- Different performance specifications

All customized products are given a unique part number, fully documented and may be ordered at any time in the future. Please contact your local sales office to discuss.

Connectivity Solutions

We provide a full range of supporting cable and connector solutions for all our switching products—20 connector families with 1200+ products. We offer everything from simple mating connectors to complex cables assemblies and terminal blocks. All assemblies are manufactured by Pickering and are guaranteed to mechanically and electrically mate to our modules.



Connectors & Backshells



Multiway Cable Assemblies



RF Cable Assemblies



Connector Blocks

We also offer customized cabling and have a free online **Cable Design Tool** that can be used to create custom cable solutions for many applications.

Visit: pickeringtest.com/cdt to start your design.

Mass Interconnect

We recommend the use of a mass interconnect solution when an Interchangeable Test Adapter (ITA) is required for a PXI or LXI based test system. Our modules are fully supported by both Virginia Panel and MacPanel.

Pickering Reed Relays

We are the only switch provider with in-house reed relay manufacturing capability via our sister company, Pickering Electronics. These instrument grade reed relays feature **SoftCenter®** technology, ensuring long service life and repeatable contact performance

To learn more, please go to: pickeringrelay.com

Programming

Pickering provide kernel, IVI and VISA (NI & Keysight) drivers which are compatible with all Microsoft supported versions of Windows and popular older versions. For a list of all supporting operating systems, please see: pickeringtest.com/os

The VISA driver is also compatible with Real-Time Operating Systems such as LabVIEW RT. For other RTOS support contact Pickering. These drivers may be used with a variety of programming environments and applications including:

- **Pickering Interfaces Switch Path Manager**
- **National Instruments** products (LabVIEW, LabWindows/CVI, Switch Executive, MAX, TestStand, VeriStand, etc.)
- **Microsoft Visual Studio** products (Visual Basic, Visual C+)
- **Keysight** VEE and OpenTAP
- **Mathworks** Matlab
- **Marvin** ATEasy
- **MTQ Testsolutions** Tecap Test & Measurement Suite

Drivers for popular Linux distributions are available, other environments are also supported, please contact Pickering with specific enquiries.

We provide Soft Front Panels (SFPs) for our products for familiarity and manual control, as well as comprehensive documentation and example programs to help you develop test routines with ease.

To learn more about software drivers and development environments, please go to: pickeringtest.com/software



Signal Routing Software

Our signal routing software, Switch Path Manager, automatically selects and energizes switch paths through Pickering switching systems. Signal routing is performed by simply defining test system endpoints to be connected together, greatly accelerating Test System software development.

To learn more, please go to: pickeringtest.com/spm



Diagnostic Relay Test Tools

eBIRST Switching System Test Tools are designed specifically for our PXI, PCI or LXI products, these tools simplify switching system fault-finding by quickly testing the system and graphically identifying the faulty relay.

To learn more, please go to: pickeringtest.com/ebirst




Three Year Warranty & Guaranteed Long-Term Support

All standard products manufactured by Pickering Interfaces are warranted against defective materials and workmanship for a period of three years from the date of delivery to the original purchaser. Extended warranty and service agreements are available for all our modules and systems with various levels to suit your requirements. Although we offer a 3-year warranty as standard, we also include guaranteed long-term support—with a history of supporting our products for typically 15-20 years. To learn more, please go to: pickeringtest.com/support

Available Product Resources

We have a large library of product resources including success stories, product and support videos, articles, as well as complete product catalogs and product reference maps to assist when looking for the switching, simulation and cable and connector solutions you need. We have also published handy reference books on Switching Technology and for the PXI and LXI standards.



To view, download or request any of our product resources, please visit: pickeringtest.com/resources

© Copyright (2020) Pickering Interfaces. All Rights Reserved
Pickering Interfaces maintains a commitment to continuous product development, consequently we reserve the right to vary from the description given in this data sheet.