



- 4 Changeover RF Relays Per Module
- Up To 1 GHz Bandwidth in 50 Ω
- Up To 1 GHz Bandwidth in 75 Ω Suitable For Telecoms or Video Applications
- Tree Networks may be Constructed by Inter-Linking Individual Modules
- VISA, IVI & Kernel Drivers Supplied for Windows
- Supported by PXI or LXI Chassis
- 3 Year Warranty

The 40-710-xx4 RF switching module comprises a bank of 4 separate high performance RF changeover switches with a characteristic impedance of 50 Ω or 75 Ω . They are bi-directional with very low insertion loss and are suitable for handling signals up to 1 GHz. Applications include aerial switching and routing high frequency signals into oscilloscopes and analyzers.

Versions are available with SMZ/Type43 or Siemens 1.0/2.3 connectors. A version with BNC connectors is also offered in a 2 PXI slot module.


The 75 Ω versions are suitable for high frequency video and telecommunication signals.




Switching Diagram for 40-710-xx4, 4 x SPDT RF Relays

40-710-704 (75 Ω BNC) Performance Plots


(Plots taken from typical sample showing all connecting paths for parameter)




40-710-704 (75 Ω BNC) typical insertion loss plots for all NO and NC inputs.



40-710-704 (75 Ω BNC) typical VSWR plots for all NO and NC inputs.



40-710-704 (75 Ω BNC) typical crosstalk plots between neighbouring channels.



40-710-704 (75 Ω BNC) typical isolation plots for all NO and NC inputs.

Relay Type

The 40-710-xx4 is fitted with high reliability RF Relays, these offer long life with good low level switching performance. Spare RF Relays are built onto the circuit board to allow easy maintenance with minimum downtime.

General Specification - All Versions

Max Switching Power:	10 W
Max Switching Voltage:	30 VDC
Max Switching Current:	0.5 A
Nominal Switching Capacity:	0.01 A, 24 VDC, 10 W@1.2 GHz
Initial On Path Resistance:	<200 mΩ
Off Path Resistance:	>1x10 ⁸ Ω
Thermal Offset:	<20 μV
Expected Life, Mechanical:	>1x10 ⁶ ops
Expected Life, Electrical:	>3x10 ⁵ ops (10 mA@24 VDC) >3x10 ⁵ ops (1 W@2.6 GHz)
Switching Time:	10 ms
Rise Time:	<0.2 ns (50 Ω), <0.3 ns (75 Ω)

50 Ω Specification - BNC Version

Bandwidth:	1 GHz
Max Switching Power:	10 W
Isolation:	Typically >27 dB (0-1 GHz)
Crosstalk:	Typically <-46 dB (0-1 GHz)
Insertion Loss:	Typically <3 dB (0-1 GHz)
VSWR:	<1.7:1

75 Ω Specification - All Versions

Bandwidth:	1 GHz
Max Switching Power:	10 W
Isolation:	Typically >30 dB (0-1 GHz)
Crosstalk:	Typically <-40 dB (0-1 GHz)
Insertion Loss:	Typically <3 dB (0-1 GHz)
VSWR:	<2.4:1

Power Requirements

+3.3 V	+5 V	+12 V	-12 V
0	320 mA (typ 240 mA)	0	0

Mechanical Characteristics

Single slot 3U PXI (CompactPCI card), Except BNC version which is 2-slot width.

Module weight: 240 g (40-710-734).

3D models for all versions in a variety of popular file formats are available on request.

Connectors

PXI bus via 32-bit P1/J1 backplane connector.

Signals via front panel coaxial connectors:

- 40-710-504 - 12 x BNC 50 Ω
- 40-710-704 - 12 x BNC 75 Ω
- 40-710-714 - 12 x SMZ/Type43 75 Ω
- 40-710-734 - 12 x 1.0/2.3 75 Ω

Operating/Storage Conditions

Operating Conditions

Operating Temperature:	0 °C to +55 °C
Humidity:	Up to 90 % non-condensing
Altitude:	5000 m

Storage and Transport Conditions

Storage Temperature:	-20 °C to +75 °C
Humidity:	Up to 90 % non-condensing
Altitude:	15000 m

PXI & CompactPCI Compliance

The module is compliant with the PXI Specification 2.2.

Local Bus, Trigger Bus & Star Trigger are not implemented.

Uses a 33 MHz 32-bit backplane interface.

Safety & CE Compliance

All modules are fully CE compliant and meet applicable

EU directives: Low-voltage safety EN61010-1:2010,

EMC Immunity EN61326-1:2013,

Emissions EN55011:2009+A1:2010.

Product Order Codes

4x SPDT Switch, 1 GHz, 50 Ω , BNC	40-710-504
4x SPDT Switch, 1 GHz, 75 Ω , BNC	40-710-704
4x SPDT Switch, 1 GHz, 75 Ω , SMZ/Type 43	40-710-714
4x SPDT Switch, 1 GHz, 75 Ω , 1.0/2.3	40-710-734

Product Customization

Pickering modules are designed and manufactured on our own flexible manufacturing lines, giving complete product control and enabling simple customization to meet very specific requirements.

Customization can include:

- Alternative relay types
- Mixture of relay types
- Alternative number of relays
- Different performance specifications

All customized products are given a unique part number, fully documented and may be ordered at any time in the future. Please contact your local sales office to discuss.

Support Products

Spare Relay Kits

Kits of replacement relays are available for the majority of Pickering's PXI switching products, simplifying servicing and reducing down-time.

Product	Relay Kit
40-710-xx4 50 Ω Versions	91-100-096 (Relay Kit 96)
40-710-xx4 75 Ω Versions	91-100-029 (Relay Kit 29)

For further assistance, please contact your local Pickering sales office.

Mating Connectors & Cabling

For connection accessories for the 40-710-xx4 range please refer to the [90-011D](#) RF Cable Assemblies data sheet where a complete list and documentation can be found for accessories, or refer to the Connection Solutions catalog.

Chassis Compatibility

This PXI module must be used in a suitable chassis. It is compatible with the following chassis types:

- All chassis conforming to the 3U PXI and 3U Compact PCI (cPCI) specification
- Legacy and Hybrid Peripheral slots in a 3U PXI Express (PXIe) chassis
- Pickering Interfaces LXI or LXI/USB Modular Chassis

Chassis Selection Guide

Standard PXI or hybrid PXIe Chassis from any Vendor:

- Mix our 1000+ PXI switching & simulation modules with any vendor's PXI instrumentation
- Embedded or remote Windows PC control
- Real-time Operating System Support
- High data bandwidths, especially with PXI Express
- Integrated module timing and synchronization

Pickering LXI or LXI/USB Modular Chassis—only accept our 1000+ PXI Switching & Simulation Modules:

- Ethernet or USB control enables remote operation
- Low-cost control from practically any controller
- LXI provides manual control via Web browsers
- Driverless software support
- Power sequencing immunity
- Ethernet provides chassis/controller voltage isolation
- Independence from Windows operating system



Connectivity Solutions


We provide a full range of supporting cable and connector solutions for all our switching products—20 connector families with 1200+ products. We offer everything from simple mating connectors to complex cables assemblies and terminal blocks. All assemblies are manufactured by Pickering and are guaranteed to mechanically and electrically mate to our modules.



Connectors & Backshells



Multiwire Cable Assemblies



RF Cable Assemblies



Connector Blocks

We also offer customized cabling and have a free online **Cable Design Tool** that can be used to create custom cable solutions for many applications. Visit: pickeringtest.com/cdt to start your design.

Mass Interconnect

We recommend the use of a mass interconnect solution when an Interchangeable Test Adapter (ITA) is required for a PXI or LXI based test system. Our modules are fully supported by both Virginia Panel and MacPanel.

Pickering Reed Relays

We are the only switch provider with in-house reed relay manufacturing capability via our Relay Division. These instrument grade reed relays feature **SoftCenter™** technology, ensuring long service life and repeatable contact performance. To learn more, please go to: pickeringrelay.com



Programming

Pickering provide kernel, IVI and VISA (NI & Keysight) drivers which are compatible with all Microsoft supported versions of Windows and popular older versions. For a list of all supporting operating systems, please see: pickeringtest.com/os

The VISA driver is also compatible with Real-Time Operating Systems such as LabVIEW RT. For other RTOS support contact Pickering. These drivers may be used with a variety of programming environments and applications including:


- **Pickering Interfaces Switch Path Manager**
- **National Instruments** products (LabVIEW, LabWindows/CVI, Switch Executive, MAX, TestStand, VeriStand, etc.)
- **Microsoft Visual Studio** products (Visual Basic, Visual C++)
- **Keysight** VEE and OpenTAP
- **Mathworks** Matlab
- **Marvin** ATEasy
- **MTQ Testsolutions** Tecap Test & Measurement Suite

Drivers for popular Linux distributions are available, other environments are also supported, please contact Pickering with specific enquiries. We provide Soft Front Panels (SFPs) for our products for familiarity and manual control, as well as comprehensive documentation and example programs to help you develop test routines with ease.

To learn more about software drivers and development environments, please go to: pickeringtest.com/software

Signal Routing Software

Our signal routing software, Switch Path Manager, automatically selects and energizes switch paths through Pickering switching systems. Signal routing is performed by simply defining test system endpoints to be connected together, greatly accelerating Test System software development. To learn more, please go to: pickeringtest.com/spm



Diagnostic Relay Test Tools

eBIRST Switching System Test Tools are designed specifically for our PXI, PCI or LXI products, these tools simplify switching system fault-finding by quickly testing the system and graphically identifying the faulty relay.

To learn more, please go to: pickeringtest.com/ebirst



Three Year Warranty & Guaranteed Long-Term Support

All standard products manufactured by Pickering Interfaces are warranted against defective materials and workmanship for a period of three years from the date of delivery to the original purchaser. Extended warranty and service agreements are available for all our modules and systems with various levels to suit your requirements. Although we offer a 3-year warranty as standard, we also include guaranteed long-term support—with a history of supporting our products for typically 15-20 years. To learn more, please go to: pickeringtest.com/support

Available Product Resources

We have a large library of product resources including success stories, product and support videos, articles and white papers as well as application specific product brochures to assist when looking for the switching, simulation and connection solutions you need. We have also published handy reference books on Switching Technology and for the PXI and LXI standards.



To view, download or request any of our product resources, please visit: pickeringtest.com/resources